Numatic

TECHNICAL SHEET

Hazardous Class

Name	HZ.370-2
Reference	877037
EAN code	5028965625927
Power supply	
Power supply type	230v AC 50/60Hz
Rated Motor Power	1000W
Protection class	Class I
Airflow Motor only	48 L/sec
Max Sealed Suction H²0	2500mm
Max Air Flow (Motor Only)	173 m³/h
Max Air Flow (In Product)	119 m³/h
MAX Under Pressure	260 (hPa)
Low Flow Operation	16L/sec (0.96m³/min)
(NB 16L/sec corresponds to an airspeed of 20m/sec in a 32mm pipe)	
Sound Pressure (LpA) Uncertainty (KpA)	65 dB (A) 0.5 dB
Cable length	10m
Cleaning Range	26.4m
Cable Type	HO5VV-F
NUPLUG system	Yes
Capacity / Weight Size	
Drum Capacity (DRY)	15L
Weight (Ready to Work)	11.46kg
Packed Weight	13.85kg
Width	355mm
Length	355mm
Height	570mm
Filtration	
Hazardous Class (EN60335-2-69)	H CLass
Filter Type (901649 Cartridge)	H13 (EN1822)
Hepa Dust Bag	NVM-2BH
Filter	TriTex
Kit AA18 (2.2P) (Included Accessories)	
915907 Parallel Hose 32mm (BoFlex) 2.2m	
602161 152mm Rubber Brush Soft Bristles (NVM-61B)	
602159 38/32mm Adaptor (NVB-59B)	
601141 Double Taper hose/ Tool Adaptor	
601142 240mm Crevice Tool	
601144 65mm Soft Dusting Brush	
601917 280mm Stainless Steel Gulper/Scraper Tool (NVA-17B)	
604016 10 x (NVM-2BH Hepa/Flo Dust Bags	
908229 Roll of 10 x 120L Waste Bags (700 x 1100mm), Grey	
604165 TriTex Filter for 305mm Machine	

Specification subject to change without prior notice

DRY VACUUM

The HZ370 forms a valuable part of any environment where the control of hazardous and health endangering dusts is required.

With a compact 370 container design, the HZ370 can be neatly stored away and ready when you need it.

H-Class Compliant
Compact & Ready
Take Control
High Efficiency
Powerful & Professional

H CLASS

H
CLASS

Suitable for:-
Asbestos.

These are suggested possible uses. Check local H&S/Statutory regulations for the type of machine required for a specific use or dust type in your area /country as regulations may differ.

DRY